



Specialty Steel

Safety Data Sheet (SDS)

Section 1 – Identification

1(a) Product Identifier used on Label: Specialty Steel

1(b) Other means of identification: Austenitic Grades, Ferrite & Martensitic Grades, Precipitation Hardening Grades, High Temp Grades, CrNiMn Grades, Low Alloy (VAR) Grades, Premium VIM Melt, Tool Steel Grades (Refer to Section 16)

1(c) Recommended use of the chemical and restrictions on use: None - Use in a manner in which this product is intended and appropriate.

1(d) Name, address, and telephone number:

Universal Stainless & Alloy Products, Inc. Phone: (412) 257-7600
600 Mayer Street
Bridgeville, PA 15017-2777

1(e) Emergency Phone Number: (412) 257-7600

Section 2 – Hazard(s) Identification

2(a) Classification of the chemical: Specialty Steel is considered an article under Reach regulation (REACH REGULATION (EC) No 1907/2006) and is not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008). However, Specialty Steel is not exempt as an article under OSHA's Hazard Communication Standard (29 CFR 1910.1200) due to its downstream use, thus this product is considered a mixture and a hazardous material. Therefore, the categories of Health Hazards as defined in "GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELING OF CHEMICALS (GHS), Third revised edition ST/SG/AC.10/30/Rev. 3" United Nations, New York and Geneva, 2009 have been evaluated. Refer to Section 3, 8 and 11 for additional information.

2(b) Signal word, hazard statement(s), symbols and precautionary statement(s):

| Hazard Symbol | Hazard Classification | Signal Word | Hazard Statement(s) |
|---------------|---|-------------|--|
| | Carcinogenicity - 1B | DANGER | May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful if swallowed or inhaled. May cause an allergic skin reaction. May cause respiratory irritation. Causes eye irritation. |
| | Reproductive Toxicity - 2 | | |
| | Single Target Organ Toxicity (STOT) Repeat Exposure - 1 | | |
| | Respiratory Sensitization - 1B | | |
| | Acute Toxicity-Oral/Inhalation - 4 | | |
| | Skin Sensitization - 1 | | |
| | Single Target Organ Toxicity (STOT) Repeat Exposure - 3 | | |
| NA | Eye Irritation - 2B | | |

Precautionary Statement(s):

| Prevention | Response | Storage/Disposal |
|---|---|--|
| Do not breathe dusts or fumes. In case of inadequate ventilation, wear respiratory protection. Wear protective gloves / protective clothing / eye protection / face protection. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Do not eat, drink or smoke when using this product. In case of inadequate ventilation, wear respiratory protection. | If exposed, concerned or feel unwell: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. If you feel unwell or are experiencing respiratory symptoms: Call a poison center or doctor/physician. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse. If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth. | Dispose of contents in accordance with federal, state and local regulations. Store locked up. |

2(c) Hazards not otherwise classified: None Known

2(d) Unknown acute toxicity statement (mixture): None Known

Section 3 – Composition/Information on Ingredients

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration:

| Chemical Name | CAS Number | EC Number | % weight |
|---------------|------------|-----------|-----------|
| Iron | 7439-89-6 | 231-096-4 | 0-98 |
| Nickel | 7440-02-0 | 231-111-4 | 0.05-60.5 |
| Cobalt | 7440-48-4 | 231-158-0 | 0.6-20.82 |
| Copper | 7440-50-8 | 231-159-6 | 0.03-6.5 |

Section 3 – Composition/Information on Ingredients (continued)

3(a-c) Chemical name, common name (synonyms), CAS number and other identifiers, and concentration (continued):

| Chemical Name | CAS Number | EC Number | % weight |
|---------------|------------|-----------|------------|
| Manganese | 7439-96-5 | 231-105-1 | 0.1-17.5 |
| Aluminum | 7429-90-5 | 231-072-3 | 0.01-3.3 |
| Nitrogen | 7727-37-9 | 231-783-9 | 0.005-2.45 |
| Sulfur | 7704-34-9 | 231-722-6 | 0.001-2.45 |

Chemical Identity of Substances Not Regulated under 29 CFR 1910.1200 (Hazard Communication Standard), but offered as information for grade(s):

| Chemical Name | CAS Number | EC Number | % weight |
|---------------|------------|-----------|------------|
| Chromium | 7440-47-3 | 231-157-5 | 0.1-35 |
| Molybdenum | 7439-98-7 | 231-107-2 | 0.01-13.5 |
| Tungsten | 7440-33-7 | 231-143-9 | 0.2-22.85 |
| Silicon | 7440-21-3 | 231-130-8 | 0.05-7.5 |
| Carbon | 7440-44-0 | 231-153-3 | 0.01-4.8 |
| Phosphorous | 7723-14-0 | 231-768-7 | 0.015-2.15 |
| Titanium | 7440-32-6 | 231-142-3 | 0.02-5.1 |
| Niobium | 7440-03-1 | 231-113-5 | 0.02-8.5 |
| Vanadium | 7440-62-2 | 231-171-1 | 0.02-8 |
| Boron | 7440-42-8 | 231-151-2 | 0.001-2.02 |

EC - European Community

CAS - Chemical Abstract Service

Note: 303SE and 440FSE grades may contain trace amounts (<0.1%) of selenium, and 2304 and 13-5-2 grades may contain trace amounts (<0.1%) of tin

Section 4 – First-aid Measures

4(a) Description of necessary measures: If exposed, concerned or feel unwell: Get medical advice/attention.

- **Inhalation: Specialty Steel** as sold/shipped is not a likely form of exposure. If inhaled: Remove person to fresh air and keep comfortable for breathing. If you feel unwell or are experiencing respiratory symptoms: Call a poison center or doctor/physician
- **Eye Contact: Specialty Steel** as sold/shipped is not a likely form of exposure. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- **Skin Contact:** If on skin: Wash with plenty of water. If irritation or rash occurs: Get medical advice/attention. Take off and wash contaminated clothing before reuse.
- **Ingestion: Specialty Steel** as sold/shipped is not a likely form of exposure. If swallowed: Call a poison center or doctor/physician if you feel unwell. Rinse mouth.

4(b) Most important symptoms/effects, acute and delayed (chronic):

- **Inhalation: Specialty Steel** as sold/shipped is not likely to present an acute or chronic health effect.
- **Eye: Specialty Steel** as sold/shipped is not likely to present an acute or chronic health effect.
- **Skin: Specialty Steel** as sold/shipped is not likely to present an acute or chronic health effect.
- **Ingestion: Specialty Steel** as sold/shipped is not likely to present an acute or chronic health effect.

However, during further processing (welding, grinding, burning, etc.) individual components may illicit an acute or chronic health effect. Refer to Section 11-Toxicological Information.

4(c) Immediate Medical Attention and Special Treatment: None Known

Section 5 – Fire-fighting Measures

5(a) Suitable (and unsuitable) Extinguishing Media: Not Applicable for **Specialty Steel** as sold/shipped. Use extinguishers appropriate for surrounding materials.

5(b) Specific Hazards arising from the chemical: Not Applicable for **Specialty Steel** as sold/shipped. When burned, toxic smoke, fume and vapor may be emitted.

5(c) Special protective equipment and precautions for fire-fighters: Self-contained NIOSH approved respiratory protection and full protective clothing should be worn when fumes and/or smoke from fire are present. Heat and flames cause emittance of acrid smoke and fumes. Do not release runoff from fire control methods to sewers or waterways. Firefighters should wear full face-piece self-contained breathing apparatus and chemical protective clothing with thermal protection. Direct water stream will scatter and spread flames and, therefore, should not be used.

Section 6 - Accidental Release Measures

6(a) Personal Precautions, Protective Equipment and Emergency Procedures: Not Applicable for **Specialty Steel** as sold/shipped. For spills involving finely divided particles, clean-up personnel should be protected against contact with eyes and skin. If material is in a dry state, avoid inhalation of dust.

Section 6 - Accidental Release Measures (continued)

6(b) Methods and materials for containment and clean up: Not Applicable for **Specialty Steel** as sold/shipped. Collect material in appropriate, labeled containers for recovery or disposal in accordance with federal, state, and local regulations. Follow applicable OSHA regulations (29 CFR 1910.120) and all other pertinent state and federal requirements.

Section 7 - Handling and Storage

7(a) Precautions for safe handling: Not Applicable for **Specialty Steel** as sold/shipped, however further processing (welding, burning, grinding, etc.) with the potential for generating high concentrations of airborne particulates should be evaluated and controlled as necessary. Wear protective gloves / protective clothing / eye protection / face protection. Contaminated work clothing must not be allowed out of the workplace. Wash thoroughly after handling. In case of inadequate ventilation, wear respiratory protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Practice good housekeeping. Do not breathe breathing metal fumes and/or dust. Do not eat, drink or smoke when using this product. Cut resistant gloves and sleeves should be worn when working with steel products.

7(b) Conditions for safe storage, including any incompatibilities: Store away from acids and incompatible materials.

Section 8 - Exposure Controls / Personal Protection

8(a) Occupational Exposure Limits (OELs): **Specialty Steel** as sold/shipped in its physical form does not present an inhalation, ingestion or contact hazard, nor would any of the following exposure data apply. However, operations such as burning, welding (high temperature), sawing, brazing, machining, grinding, etc may produce fumes and/or particulates. The following exposure limits are offered as reference for an experienced industrial hygienist to review:

| Ingredients | OSHA PEL ¹ | ACGIH TLV ² | NIOSH REL ³ | IDLH ⁴ |
|-------------|--|---|--|---------------------------------|
| Iron | 10 mg/m ³ (iron oxide fume) | 5.0 mg/m ³ (iron oxide, respirable fraction ⁷) | 5.0 mg/m ³ (iron oxide dust and fume) | 2,500 mg/m ³ (as Fe) |
| Nickel | 1.0 mg/m ³ (metal, insoluble & soluble compounds, as Ni) | 1.5 mg/m ³ (metal, as Ni, as inhalable fraction ⁵) 0.2 mg/m ³ (insoluble compounds, as Ni, inhalable fraction, inorganic only) 0.1 mg/m ³ (soluble compounds, as Ni, inhalable fraction, inorganic only) | 0.015 mg/m ³ (metal & insoluble and soluble compounds, as Ni) | 10 mg/m ³ (as Ni) |
| Cobalt | 0.1 mg/m ³ (inorganic compounds, as Co, metal dust & fume) | 0.02 mg/m ³ (inorganic compounds, as Co) | 0.05 mg/m ³ (inorganic compounds, as Co, metal dust & fume) | 20 mg/m ³ (as Co) |
| Copper | 0.1 mg/m ³ (as fume, Cu) 1.0 mg/m ³ (as dusts & mists, Cu) | 0.2 mg/m ³ (as fume) 1.0 mg/m ³ (as dusts & mists, Cu) | 0.1 mg/m ³ (as fume, Cu) 1.0 mg/m ³ (as dusts & mists, Cu) | 100 mg Cu/m ³ |
| Manganese | "C" 5.0 mg/m ³ (as fume & inorganic compounds, as Mn) | 0.02 mg/m ³ (as fume & inorganic compounds, as Mn, respirable fraction) 0.1 mg/m ³ (as fume & inorganic compounds, as Mn, inhalation fraction) | 1.0 mg/m ³ (as fume & inorganic compounds, as Mn) "STEL" 3.0 mg/m ³ (as fume & inorganic compounds, as Mn) | 500 mg/m ³ (as Mn) |
| Aluminum | 15 mg/m ³ (as oxide, metal and insoluble compounds, total dust, PNOR ⁶) 5.0 mg/m ³ (as oxide, metal and insoluble compounds, respirable fraction, PNOR) | 1.0 mg/m ³ (as metal and insoluble compounds, respirable fraction) | 15 mg/m ³ (as metal and insoluble compounds, total dust) 5.0 mg/m ³ (as metal and insoluble compounds, respirable fraction) | NE |
| Nitrogen | NE | NE | NE | NE |
| Sulfur | 15 mg/m ³ (total dust, PNOR) 5.0 mg/m ³ (as respirable fraction, PNOR) | 10 mg/m ³ (as inhalable fraction, PNO ⁸) 3.0 mg/m ³ (as respirable fraction, PNO ⁸) | NE | NE |

NE - None Established

1. OSHA Permissible Exposure Limits (PELs) are 8-hour TWA (time-weighted average) concentrations unless otherwise noted. A (C) designation denotes a ceiling limit, which should not be exceeded during any part of the working exposure unless otherwise noted. A Peak is defined as the acceptable maximum peak for a maximum duration above the ceiling concentration for an eight-hour shift. A skin notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. A Short Term Exposure Limit (STEL) is defined as a 15-minute exposure, which should not be exceeded at any time during a workday. An Action level (AL) is used by OSHA and NIOSH to express a health or physical hazard. They indicate the level of a harmful or toxic substance/activity, which requires medical surveillance, increased industrial hygiene monitoring, or biological monitoring. Action Levels are generally set at one half of the PEL but the actual level may vary from standard to standard. The intent is to identify a level at which the vast majority of randomly sampled exposures will be below the PEL.
2. Threshold Limit Values (TLV) established by the American Conference of Governmental Industrial Hygienists (ACGIH) are 8-hour TWA concentrations unless otherwise noted. A Short Term Exposure Limit (STEL) is defined as the maximum concentration to which workers can be exposed for a short period of time (15 minutes) for only four times throughout the day with at least one hour between exposures. A "skin" notation refers to the potential significant contribution to the overall exposure by the cutaneous route, either by contact with vapors or, of probable greater significance, by direct skin contact with the substance. ACGIH-TLVs are only recommended guidelines based upon consensus agreement of the membership of the ACGIH. As such, the ACGIH TLVs are for guideline use purposes and are not legal regulatory standards for compliance purposes. The TLVs are designed for use by individuals trained in the discipline of industrial hygiene relative to the evaluation of exposure to various chemical or biological substances and physical agents that may be found in the workplace.
3. The National Institute for Occupational Safety and Health Recommended Exposure Limits (NIOSH-REL) - Compendium of Policy and Statements. NIOSH, Cincinnati, OH (1992). NIOSH is the federal agency designated to conduct research relative to occupational safety and health. As is the case with ACGIH TLVs, NIOSH RELs are for guideline purposes only and as such are not legal, regulatory limits for compliance purposes.

Section 8 - Exposure Controls / Personal Protection (continued)

8(a) Occupational Exposure Limits (OELs) (continued):

4. The "immediately dangerous to life or health air concentration values (IDLHs)" are used by NIOSH as part of the respirator selection criteria and were first developed in the mid-1970's by NIOSH. The Documentation for Immediately Dangerous to Life or Health Concentrations (IDLHs) is a compilation of the rationale and sources of information used by NIOSH during the original determination of 387 IDLHs and their subsequent review and revision in 1994.
5. Inhalable fraction. The concentration of inhalable particulate for the application of this TLV is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2018 TLVs[®] and BEIs[®] (Biological Exposure Indices) Appendix D, paragraph A.
6. PNOR (Particulates Not Otherwise Regulated). All inert or nuisance dusts, whether mineral, inorganic, or organic, not listed specifically by substance name are covered by the PNOR limit which is the same as the inert or nuisance dust limit of 15 mg/m³ for total dust and 5.0 mg/m³ for the respirable fraction (containing no detectable crystalline silica).
7. Respirable fraction - The concentration of respirable dust for the application of this limit is to be determined from the fraction passing a size-selector with the characteristics defined in the ACGIH 2018 TLVs[®] and BEIs[®] Appendix D, paragraph C.
8. PNOS (Particulates Not Otherwise Specified). Particulates identified under the PNOS heading are "nuisance dusts" containing no asbestos and <1% crystalline silica.

8(b) Appropriate Engineering Controls: Use controls as appropriate to minimize exposure to metal fumes and dusts during handling operations. Provide general or local exhaust ventilation systems to minimize airborne concentrations. Local exhaust is necessary for use in enclosed or confined spaces. Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below current exposure limits.

8(c) Individual Protection Measures:

- **Respiratory Protection:** Seek professional advice prior to respirator selection and use. Follow OSHA respirator regulations (29 CFR 1910.134) and, if necessary, use only a NIOSH-approved respirator. Select respirator based on its suitability to provide adequate worker protection for given working conditions, level of airborne contamination, and presence of sufficient oxygen. Concentration in air of the various contaminants determines the extent of respiratory protection needed. Half-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 10 times the exposure limit. Full-face, negative-pressure, air-purifying respirator equipped with P100 filter is acceptable for concentrations up to 50 times the exposure limit. Protection by air-purifying negative-pressure and powered air respirators is limited. Use a positive-pressure-demand, full-face, supplied air respirator or self-contained breathing apparatus (SCBA) for concentrations above 50 times the exposure limit. If exposure is above the IDLH (Immediately dangerous to life or health) for any of the constituents, or there is a possibility of an uncontrolled release or exposure levels are unknown, then use a positive-demand, full-face, supplied air respirator with escape bottle or SCBA.

Warning! Air-purifying respirators both negative-pressure and powered-air do not protect workers in oxygen-deficient atmospheres.

- **Eyes:** Wear appropriate eye protection to prevent eye contact. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use safety glasses to prevent eye contact. Contact lenses should not be worn where industrial exposures to this material are likely. Use safety glasses or goggles as required for welding, burning, sawing, brazing, grinding or machining operations.
- **Skin:** Wear appropriate personal protective clothing to prevent skin contact. Cut resistant gloves and sleeves should be worn when working with steel products. For operations which result in elevating the temperature of the product to or above its melting point or result in the generation of airborne particulates, use protective clothing, and gloves to prevent skin contact. Protective gloves should be worn as required for welding, burning or handling operations. Contaminated work clothing must not be allowed out of the workplace.
- **Other protective equipment:** An eyewash fountain and deluge shower should be readily available in the work area.

Section 9 - Physical and Chemical Properties

- | | |
|--|--|
| 9(a) Appearance (physical state, color, etc.): Solid with metallic luster | 9(j) Upper/lower Flammability or Explosive Limits: NA |
| 9(b) Odor: Odorless | 9(k) Vapor Pressure: ND |
| 9(c) Odor Threshold: NA | 9(l) Vapor Density (Air = 1): NA |
| 9(d) pH: NA | 9(m) Relative Density: Approx. 8 |
| 9(e) Melting Point/Freezing Point: ND | 9(n) Solubility(ies): Water Insoluble |
| 9(f) Initial Boiling Point and Boiling Range: ND | 9(o) Partition Coefficient n-octanol/water: ND |
| 9(g) Flash Point: NA | 9(p) Auto-ignition Temperature: NA |
| 9(h) Evaporation Rate: NA | 9(q) Decomposition Temperature: ND |
| 9(i) Flammability (solid, gas): Non-flammable, non-combustible | 9(r) Viscosity: NA |

NA - Not Applicable








ND - Not Determined for product as a whole

Section 10 - Stability and Reactivity

- 10(a) Reactivity:** Not Determined (ND) for product in a solid form. Do not use water on molten metal.
- 10(b) Chemical Stability:** Steel products are stable under normal storage and handling conditions.
- 10(c) Possibility of hazardous reaction:** None Known
- 10(d) Conditions to Avoid:** Storage with strong acids or calcium hypochlorite.
- 10(e) Incompatible Materials:** Will react with strong acids to form hydrogen. Iron oxide dusts in contact with calcium hypochlorite evolve oxygen and may cause an explosion.
- 10(f) Hazardous Decomposition Products:** Thermal oxidative decomposition of steel products can produce fumes containing oxides of iron and manganese as well as other alloying elements.

Section 11 - Toxicological Information

11 Information on toxicological effects: The following toxicity data has been determined for **Specialty Steel** when further processed using the information available for its components applied to the guidance on the preparation of an SDS under the GHS requirements of OSHA and the EU CPL:

| Hazard Classification | Hazard Category | | Hazard Symbols | Signal Word | Hazard Statement |
|--|-----------------|-----------------|---|----------------|--|
| | EU | OSHA | | | |
| Acute Toxicity Hazard (covers Categories 1-4) | NA* | 4 ^a |  | Warning | Harmful if swallowed or inhaled. |
| Eye Damage/Irritation (covers Categories 1, 2A & 2B) | NA* | 2B ^c | NA | Warning | Causes eye irritation. |
| Skin/Dermal Sensitization (covers Category 1) | NA* | 1 ^d |  | Warning | May cause an allergic skin reaction. |
| Respiratory Sensitization (covers Category 1A & 1B) | NA* | 1B ^d |  | Warning | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| Carcinogenicity (covers Categories 1A, 1B and 2) | NA* | 1B ^e |  | Warning | May cause cancer. |
| Toxic Reproduction (covers Categories 1A, 1B and 2) | NA* | 2 ^h |  | Warning | Suspected of damaging fertility or the unborn child. |
| Specific Target Organ Toxicity (STOT) Following Single Exposure (covers Categories 1-3) | NA* | 3 ⁱ |  | Warning | May cause respiratory irritation. |
| STOT following Repeated Exposure (covers Categories 1 and 2) | NA* | 1 ^j |  | Danger | Causes damage to lungs and central nervous system through prolonged or repeated inhalation exposure. |

* Not Applicable - Semi-formed steel products are considered articles under Reach regulation (REACH REGULATION (EC) No 1907/2006) and are not subject to classification under CLP regulation (REGULATION (EC) No 1272/2008).

Toxicological data listed below are presented regardless to classification criteria. Individual hazard classification categories where the toxicological information has met or exceeded a classification criteria threshold are listed above.

a. No LC₅₀ or LD₅₀ has been established for **Specialty Steel**. The following data has been determined for the components:

- **Nickel:** LD₅₀ >9000 mg/kg (Oral/Rat)
- **Copper:** Rat LD₅₀ = 481 mg/kg (REACH)
Rat LD₅₀ > 2500 mg/kg (REACH)
- **Manganese:** Rat LD₅₀ > 2000 mg/kg (REACH)
Rat LD₅₀ > 9000 mg/kg (NLM Toxnet)
- **Cobalt:** LD₅₀ = 10 mg/L(rat)
LD₅₀ = 500 mg/kg (Oral/Rat)
- **Iron:** Rat LD₅₀ =98.6 g/kg (REACH)
Rat LD₅₀ =1060 mg/kg (IUCLID)
Rat LD₅₀ =984 mg/kg (IUCLID)
Rabbit LD₅₀ =890 mg/kg (IUCLID)
- **Aluminum:** Rat LD₅₀ > 15.9 g/kg (REACH)
- **Manganese:** Rat LD₅₀ > 2000 mg/kg (REACH)
Rat LD₅₀ > 9000 mg/kg (NLM Toxnet)

b. No Skin (Dermal) Irritation data available for **Specialty Steel** as a mixture. The following Skin (Dermal) Irritation information was found for the components:

- **Sulfur:** Rabbit irritation, edema and erythema 4 at 72 hours all resolved by day 7. (REACH)

c. No Eye Irritation data available for **Specialty Steel** as a mixture. The following Eye Irritation information was found for the components:

- **Iron:** Causes eye irritation.
- **Nickel:** Slight eye irritation from particulate abrasion only.

d. No Skin (Dermal)/respiratory Sensitization data available for **Specialty Steel** as a mixture. The following Skin (Dermal) Sensitization information was found for the components:

- **Nickel:** May cause allergic skin sensitization.
- **Cobalt:** Skin Sensitizing In vitro mouse local lymph node. Guinea Pig Maximization test and patch test - sensitizing.

e. No Respiratory Sensitization data available for **Specialty Steel** as a mixture or its components.

f. No Germ Cell Mutagenicity data available for **Specialty Steel** as a mixture. The following Mutagenicity and Genotoxicity information was found for the components:

- **Nickel:** EU RAR has found positive results in vitro and in vivo but insufficient data for classification.
- **Iron:** IUCLID has found some positive and negative findings in vitro.

Section 11 - Toxicological Information (continued)

11 Information on toxicological effects (continued):

- g. Carcinogenicity: IARC, NTP, and OSHA do not list **Specialty Steel** as carcinogens. The following Carcinogenicity information was found for the components:
- **Nickel and certain nickel compounds** – IARC-1 (compounds), carcinogen to humans; IARC-2B (elemental & alloys), possibly carcinogenic to humans; ACGIH TLV-A1 (insoluble compounds, as Ni), confirmed human carcinogen; TLV-A5 (elemental), not suspected as a human carcinogen; NTP-K, known to be a carcinogen; NIOSH-Ca, potential occupational carcinogen.
 - **Chromium (as metal and trivalent chromium compounds)** – IARC-3 (organic & inorganic compounds), unclassifiable as to carcinogenicity in humans; ACGIH TLV-A4, not classifiable as a human carcinogen; EPA-D, not classifiable as to human carcinogenicity (CBD, cannot be determined).
 - **Chromium (hexavalent)** - IARC-1, carcinogen to humans; ACGIH TLV-A1, confirmed human carcinogen; NIOSH-Ca, potential occupational carcinogen; NTP-K, known to be a carcinogen; EPA-A, human carcinogen (by inhalation route of entry), EPA-K, cannot be determined, not classifiable as to human carcinogenicity.
 - **Welding Fumes** - IARC-2B, possibly carcinogenic to humans; NIOSH-Ca, potential occupational carcinogen.
 - **Cobalt** – IARC-2B, possibly carcinogenic to humans; ACGIH TLV-A3 (inorganic compounds), confirmed animal carcinogen with unknown relevance to humans; NTP-R (that releases cobalt ions in vivo), reasonably anticipated to be a human carcinogen (RAHC).
- h. No Toxic Reproduction data available for **Specialty Steel** as a mixture. The following Toxic Reproductive information was found for the components:
- **Nickel**: Effects on fertility.
- i. No Specific Target Organ Toxicity (STOT) following a Single Exposure data available for **Specialty Steel** as a mixture. The following STOT following a Single Exposure data was found for the components:
- **Iron and Molybdenum**: Irritating to Respiratory tract.
 - **Aluminum**: Repeated exposure associated with asthma, fibrosis in lungs and encephalopathy in humans.
- j. No Specific Target Organ Toxicity (STOT) following Repeated Exposure data was available for **Specialty Steel** as a whole. The following STOT following Repeated Exposure data was found for the components:
- **Nickel**: Rat 4 wk inhalation LOEL 4 mg/m³ Lung and Lymph node histopathology. Rat 2 yr inhalation LOEL 0.1 mg/m³ Pigment in kidney, effects on hematopoiesis spleen and bone marrow and adrenal tumor. Rat 13 Week Inhalation LOAEC 1.0 mg/m³ Lung weights, and Alveolar histopathology.
 - **Copper**: Target organs affected - Skin, eyes liver, kidneys and respiratory tract.
 - **Manganese**: Inhalation of metal fumes - Degenerative changes in human Brain; Behavioral: Changes in motor activity and muscle weakness (Whitlock *et al.*, 1966).
 - **Aluminum**: Reviews have found chronic exposure to aluminum flake has been reported to cause pneumoconiosis in workers. Repeat oral exposure to aluminum results in decrements in neurobehavioral function and development.

The above toxicity information was determined from available scientific sources to illustrate the prevailing posture of the scientific community. The scientific resources includes: The American Conference of Governmental Industrial Hygienist (ACGIH) Documentation of the Threshold Limit Values (TLVs) and Biological Exposure indices (BEIs) with Other Worldwide Occupational Exposure Values 2018, The International Agency for Research on Cancer (IARC), The National Toxicology Program (NTP) updated documentation, the World Health Organization (WHO) and other available resources, the International Uniform Chemical Information Database (IUCLID), European Union Risk Assessment Report (EU-RAR), Concise International Chemical Assessment Documents (CICAD), European Union Scientific Committee for Occupational Exposure Limits (EU-SCOEL), Agency for Toxic Substances and Disease Registry (ATSDR), Hazardous Substance Data Bank (HSDB), and International Programme on Chemical Safety (IPCS).

The following health hazard information is provided regardless to classification criteria and is based on the individual component(s) and potential resultant components from further processing:

Acute Effects:

- **Inhalation**: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes, skin and mucous membranes of the upper respiratory tract. Excessive inhalation of fumes of freshly formed metal oxide particles sized below 1.5 micrometer and usually between 0.02-0.05 micrometers from many metals can produce an acute reaction known as “metal fume fever”. Symptoms consist of chills and fever (very similar to and easily confused with flu symptoms), metallic taste in the mouth, dryness and irritation of the throat followed by weakness and muscle pain. The symptoms come on in a few hours after excessive exposures and usually last from 12 to 48 hours. Long-term effects from metal fume fever have not been noted.
- **Eye**: Excessive exposure to high concentrations of metal dust may cause irritation to the eyes.
- **Skin**: Skin contact with metal dusts may cause irritation or sensitization, possibly leading to dermatitis. Skin contact with metallic fumes and dusts may cause physical abrasion.
- **Ingestion**: Ingestion of harmful amounts of this product as distributed is unlikely due to its solid insoluble form. Ingestion of metal dust may cause nausea or vomiting.

Acute Effects by component:

- **Iron and iron oxides**: Iron is harmful if swallowed, causes skin irritation, and causes eye irritation. Contact with iron oxide has been reported to cause skin irritation and serious eye damage. Particles of iron or iron compounds, which become imbedded in the eye, may cause rust stains unless removed fairly promptly.
- **Nickel and nickel oxides**: Nickel may cause allergic skin sensitization. Nickel oxide may cause an allergic skin.
- **Chromium and chromium oxides**: Hexavalent chrome causes damage to gastrointestinal tract, lung, severe skin burns and eye damage, serious eye damage, skin contact may cause an allergic skin reaction. Inhalation may cause allergic or asthmatic symptoms or breathing difficulties.
- **Cobalt and cobalt oxides**: May cause skin, eye and allergic skin reactions.
- **Copper and copper oxides**: Copper may cause allergic skin reaction. Copper oxide is harmful if swallowed, causes skin and eye irritation, and may cause an allergic skin reaction.

Section 11 - Toxicological Information (continued)

Acute Effects by component (continued):

- **Manganese and manganese oxides:** Manganese and Manganese oxide are harmful if swallowed.
- **Aluminum and aluminum oxides:** Inhalation may cause cough.
- **Nitrogen gas:** Simple asphyxiant.
- **Sulfur:** Sulfur is harmful if swallowed, causes skin and eye irritation.

Delayed (chronic) Effects by component:

- **Iron and iron oxides:** Chronic inhalation of excessive concentrations of iron oxide fumes or dusts may result in the development of a benign pneumoconiosis, called siderosis, which is observable as an X-ray change. No physical impairment of lung function has been associated with siderosis. Inhalation of excessive concentrations of ferric oxide may enhance the risk of lung cancer development in workers exposed to pulmonary carcinogens. Iron oxide is listed as a Group 3 (not classifiable) carcinogen by the International Agency for Research on Cancer (IARC).
- **Nickel and nickel oxides:** Exposure to nickel dusts and fumes can cause sensitization dermatitis, respiratory irritation, asthma, pulmonary fibrosis, edema, and may cause nasal or lung cancer in humans. Nickel causes damage to lungs through prolonged or repeated inhalation exposure. IARC lists nickel and certain nickel compounds as Group 2B carcinogens (sufficient animal data). ACGIH 2018 TLVs® and BEIs® lists insoluble nickel compounds as confirmed human carcinogens. Nickel is suspected of damaging the unborn child.
- **Chromium and chromium oxides:** The health hazards associated with exposure to chromium are dependent upon its oxidation state. The metal form (chromium as it exists in this product) is of very low toxicity. The hexavalent form is very toxic. Repeated or prolonged exposure to hexavalent chromium compounds may cause respiratory irritation, nosebleed, ulceration and perforation of the nasal septum. Industrial exposure to certain forms of hexavalent chromium has been related to an increased incidence of cancer. NTP (The National Toxicology Program) Fourth Annual report on Carcinogens cites "certain Chromium compounds" as human carcinogens. ACGIH has reviewed the toxicity data and concluded that chromium metal is not classifiable as a human carcinogen. Hexavalent chromium may cause genetic defects and is suspected of damaging the unborn child. Developmental toxicity in the mouse, suspected of damaging fertility or the unborn child.
- **Cobalt:** Chronic exposure to cobalt metal, dust, or fume may cause respiratory or dermatologic signs and symptoms. Following skin sensitization, contact with cobalt causes eruptions of dermatitis increases and on frictional surfaces of the arms, legs, and neck. Chronic respiratory exposure results in reduced lung function, increased fibrotic changes on chest X-ray, production of scanty mucoid sputum, and shortness of breath.
- **Copper and copper oxides:** Inhalation of high concentrations of freshly formed oxide fumes and dusts of copper can cause metal fume fever. Chronic inhalation of copper dust has caused, in animals, hemolysis of the red blood cells, deposition of hemofuscin in the liver and pancreas, injury to lung cells and gastrointestinal symptoms.
- **Manganese and manganese oxides:** Chronic exposure to high concentrations of manganese fumes and dusts may adversely affect the central nervous system with symptoms including languor, sleepiness, weakness, emotional disturbances, spastic gait, mask-like facial expression and paralysis. Animal studies indicate that manganese exposure may increase susceptibility to bacterial and viral infections. Occupational overexposure (Manganese) is a progressive, disabling neurological syndrome that typically begins with relatively mild symptoms and evolves to include altered gait, fine tremor, and sometimes, psychiatric disturbances. May cause damage to lungs with repeated or prolonged exposure. Neurobehavioral alterations in worker populations exposed to MnO including: speed and coordination of motor function are especially impaired.
- **Aluminum and aluminum oxides:** Considered to be an inert or nuisance dust.
- **Nitrogen:** Not Reported/Not Classified
- **Sulfur:** Sulfur compounds, present in the fumes, may irritate the skin, eyes, lungs and gastrointestinal tract. May cause damage to the lung from prolonged or repeated exposure, Sulfur dioxide vapor is irritating to the respiratory tract and can cause lung damage with repeated or prolonged exposure.

Section 12 - Ecological Information

12(a) Ecotoxicity (aquatic & terrestrial): No Data Available for **Specialty Steel** as sold/shipped. However, individual components of the product when processed have been found to be toxic to the environment. Metal dusts may migrate into soil and groundwater and be ingested by wildlife as follows:

- **Nickel Oxide:** IUCLID found LC₅₀ in fish, invertebrates and algae > 100 mg/L.
- **Iron Oxide:** LC₅₀: >1000 mg/L; Fish 48 h-EC₅₀ > 100 mg/L (Currenta, 2008k); 96 h-LC₀ ≥ 50,000 mg/L Test substance: Bayferrox 130 red (95 – 97% Fe₂O₃; < 4% SiO₂ and Al₂O₃) (Bayer, 1989a).

12(b) Persistence & Degradability: No Data Available for **Specialty Steel** as sold/shipped or individual components.

12(c) Bioaccumulative Potential: No Data Available for **Specialty Steel** as sold/shipped or individual components.

12(d) Mobility (in soil): No data available for **Specialty Steel** as sold/shipped. However, individual components of the product have been found to be absorbed by plants from soil.

12(e) Other adverse effects: None Known

Additional Information:

Hazard Category: Not Reported

Signal Word: No Signal Word

Hazard Symbol: No Symbol

Hazard Statement: No Statement

Section 13 - Disposal Considerations

Disposal: Steel scrap should be recycled whenever possible. Product dusts and fumes from processing operations should also be recycled or classified by a competent environmental professional and disposed of in accordance with applicable federal, state or local regulations.



Specialty Steel

Safety Data Sheet (SDS)

Rev. 9/19/18

Section 13 - Disposal Considerations (continued)

Container Cleaning and Disposal: Follow applicable federal, state and local regulations. Observe safe handling precautions. European Waste Catalogue (EWC): 16-01-17 (ferrous metals), 12-01-99 (wastes not otherwise specified), 16-03-04 (off specification batches and unused products), or 15-01-04 (metallic packaging).

Please note this information is for Specialty Steel in its original form. Any alterations can void this information.

Section 14 - Transport Information

14 (a-g) Transportation Information:

US Department of Transportation (DOT) under 49 CFR 172.101 **does not** regulate **Specialty Steel** as a hazardous material. All federal, state, and local laws and regulations that apply to the transport of this type of material must be adhered to.

| | | |
|---|---|--|
| Shipping Name: Not Applicable (NA) Shipping Symbols: NA Hazard Class: NA UN No.: NA Packing Group: NA DOT/IMO Label: NA Special Provisions (172.102): NA | Packaging Authorizations a) Exceptions: NA b) Group: NA c) Authorization: NA | Quantity Limitations a) Passenger, Aircraft, or Railcar: NA b) Cargo Aircraft Only: NA Vessel Stowage Requirements a) Vessel Stowage: NA b) Other: NA DOT Reportable Quantities: NA |
|---|---|--|

International Maritime Dangerous Goods (IMDG) and the Regulations Concerning the International Carriage of Dangerous Goods by Rail (RID) classification, packaging and shipping requirements follow the US DOT Hazardous Materials Regulation.

Regulations Concerning the International Carriage of Dangerous Goods by Road (ADR) does not regulate **Specialty Steel** as a hazardous material.

| | | |
|--|--|---|
| Shipping Name: Not Applicable (NA) Classification Code: NA UN No.: NA Packing Group: NA ADR Label: NA Special Provisions: NA Limited Quantities: NA | Packaging a) Packing Instructions: NA b) Special Packing Provisions: NA c) Mixed Packing Provisions: NA | Portable Tanks & Bulk Containers a) Instructions: NA b) Special Provisions: NA |
|--|--|---|

International Air Transport Association (IATA) does not regulate **Specialty Steel** as a hazardous material.

| | | | | |
|---|---------------------------------------|-------------------------------|---|---|
| Shipping Name: Not Applicable (NA) Class/Division: NA Hazard Label (s): NA UN No.: NA Packing Group: NA Excepted Quantities (EQ): NA | Passenger & Cargo Aircraft | | Cargo Aircraft Only: Pkg Inst: NA Max Net Qty/Pkg: NA | Special Provisions: NA ERG Code: NA |
| | Limited Quantity (EQ) | | | |
| | Pkg Inst: NA | Pkg Inst: NA | | |
| | Max Net Qty/Pkg: NA | Max Net Qty/Pkg: NA | | |

Pkg Inst – Packing Instructions

Max Net Qty/Pkg – Maximum Net Quantity per Package

ERG – Emergency Response Drill Code

Transport Dangerous Goods (TDG) Classification: **Specialty Steel** does not have a TDG classification.

Section 15 - Regulatory Information

Regulatory Information: The following listing of regulations relating to a Universal Stainless & Alloy Product may not be complete and should not be solely relied upon for all regulatory compliance responsibilities. This product and/or its constituents are subject to the following regulations:

OSHA Regulations: Air Contaminant (29 CFR 1910.1000, Table Z-1, Z-2, Z-3): The product, **Specialty Steel** as a whole is not listed. However, individual components of the product are listed: Refer to Section 8, Exposure Controls and Personal Protection

EPA Regulations: The product, **Specialty Steel** is not listed as a whole. However, individual components of the product are listed:

| Components | Regulations |
|------------|-----------------------------------|
| Iron | SDWA |
| Nickel | CAA, CERCLA, CWA, SARA 313 |
| Cobalt | SARA 313 |
| Copper | CWA, SARA 313, SDWA |
| Manganese | CERCLA, CAA, SARA 313 |
| Chromium | CERCLA, CWA, SARA 313, RCRA, SDWA |

SARA 311/312 Potential Hazard Categories: Immediate Acute Health Hazard; Delayed Chronic Health Hazard.

Section 15 - Regulatory Information (continued)

EPA Regulations (continued):

Section 313 Supplier Notification: The product, **Specialty Steel** contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act and 40 CFR part 372:

| CAS # | Chemical Name | Percent by Weight |
|-----------|---------------|-------------------|
| 7440-02-0 | Nickel | 99 max |
| 7440-47-3 | Chromium | 30 max |
| 7440-48-4 | Cobalt | 30 max |
| 7440-50-8 | Copper | 30 max |
| 7439-96-5 | Manganese | 20 max |


Regulations Key:

- CAA Clean Air Act (42 USC Sec. 7412; 40 CFR Part 61 [As of: 8/18/06])
- CERCLA Comprehensive Environmental Response, Compensation and Liability Act (42 USC Secs. 9601(14), 9603(a); 40 CFR Sec. 302.4, Table 302.4, Table 302.4 and App. A)
- CWA Clean Water Act (33 USC Secs. 1311; 1314(b), (c), (e), (g); 136(b), (c); 137(b), (c) [as of 8/2/06])
- RCRA Resource Conservation Recovery Act (42 USC Sec. 6921; 40 CFR Part 261 App VIII)
- SARA Superfund Amendments and Reauthorization Act of 1986 Title III Section 302 Extremely Hazardous Substances (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65) and Section 313 Toxic Chemicals (42 USC Secs. 11023, 13106; 40 CFR sec. 372.65 [as of 6/30/05])
- TSCA Toxic Substance Control Act (15 U.S.C. s/s 2601 et seq. [1976])
- SDWA Safe Drinking Water Act (42 U.S.C. s/s 300f et seq. [1974])

State Regulations: The product, **Specialty Steel** as a whole is not listed in any state regulations. However, individual components of the product are listed in various state regulations:

Pennsylvania Right to Know: Contains regulated material in the following categories:

- Hazardous Substances: Nickel, Chromium, Cobalt, Copper, Manganese, Aluminum, Nitrogen, Sulfur
- Environmental Hazards: Nickel, Chromium, Cobalt, Copper, Manganese, Aluminum
- Special Hazardous Substance: Nickel, Chromium

California Prop. 65:  This product can expose you to chemicals including nickel and cobalt metal, which is known to the State of California to cause cancer, and hexavalent chromium which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

New Jersey: Contains regulated material in the following categories:

- Hazardous Substance: Nickel, Chromium, Cobalt, Copper, Manganese, Silicon, Aluminum (dust or fume), Tungsten
- Environmental Hazard: Nickel, Chromium, Cobalt, Copper, Manganese
- Special Hazardous Substance: Chromium, Cobalt, Manganese, Aluminum (dust or fume)

Minnesota: Nickel, Chromium, Cobalt, Manganese

Massachusetts: Nickel (compounds), Chromium, Cobalt, Copper (compounds), Manganese (compounds), Sulfur, Nitrogen, Aluminum (dust or fume)

Other Regulations:

WHMIS Classification (Canadian): The product, **Specialty Steel** is not listed as a whole. However individual components are listed.

| Ingredients | WHMIS Classification |
|-------------|---|
| Nickel | Skin sensitization – Category 1; Carcinogenicity – Category 2; Specific target organ toxicity – repeated exposure - Category 1 |
| Cobalt | Respiratory sensitization – Category 1; Skin sensitization – Category 1; Carcinogenicity – Category 2; Combustible dusts* |
| Manganese | Reproductive toxicity - Category 2; Specific target organ toxicity - repeated exposure - Category 1; Combustible dusts* |
| Sulfur | Flammable solids – Category 2; Skin corrosion/irritation – Category 2; Combustible dusts** |

*This product could belong to the hazard class "Combustible dust", based on various factors related to the combustibility and explosiveness of its dust, including composition, shape and size of the particles

**This product belongs to the hazard class "Combustible dust" if 5% or more by weight of its composition has a particle size < 500 µm.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information

Prepared By: Universal Stainless & Alloy Products, Inc.

Revision History:

- 5/29/2015 - Update to OSHA HAZCOM 2012 format
- 7/15/2016 – Update grades and WHMIS 2015
- 9/19/2018 – Update Sections 3, 8, 11 & 15

Section 16 - Other Information (continued)


Additional Information:

Hazardous Material Identification System (HMIS) Classification

| | |
|-----------------|---|
| Health Hazard | 1 |
| Fire Hazard | 0 |
| Physical Hazard | 0 |

HEALTH= 1, Denotes possible chronic hazard if airborne dusts or fumes are generated Irritation or minor reversible injury possible.
FIRE= 0, Materials that will not burn.
PHYSICAL HAZARD= 0, Materials that are normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosives.

National Fire Protection Association (NFPA)



HEALTH = 1, Exposure could cause irritation but only minor residual injury even if no treatment is given.
FLAMMABILITY = 0, Materials that will not burn.
INSTABILITY = 0, Normally stable, even under fire exposure conditions, and are not reactive with water.

ABBREVIATIONS/ACRONYMS:

| | | | |
|-------------------------|---|--------------|---|
| ACGIH | American Conference of Governmental Industrial Hygienists | NIF | No Information Found |
| BEIs | Biological Exposure Indices | NIOSH | National Institute for Occupational Safety and Health |
| CAS | Chemical Abstracts Service | NTP | National Toxicology Program |
| CERCLA | Comprehensive Environmental Response, Compensation, and Liability Act | ORC | Organization Resources Counselors |
| CFR | Code of Federal Regulations | OSHA | Occupational Safety and Health Administration |
| CNS | Central Nervous System | PEL | Permissible Exposure Limit |
| GI, GIT | Gastro-Intestinal, Gastro-Intestinal Tract | PNOR | Particulate Not Otherwise Regulated |
| HMS | Hazardous Materials Identification System | PNOC | Particulate Not Otherwise Classified |
| IARC | International Agency for Research on Cancer | PPE | Personal Protective Equipment |
| LC50 | Median Lethal Concentration | ppm | parts per million |
| LD50 | Median Lethal Dose | RCRA | Resource Conservation and Recovery Act |
| LD_{Lo} | Lowest Dose to have killed animals or humans | RTECS | Registry of Toxic Effects of Chemical Substances |
| LEL | Lower Explosive Limit | SARA | Superfund Amendment and Reauthorization Act |
| LOEL | Lowest Observed Effect Level | SCBA | Self-contained Breathing Apparatus |
| LOAEC | Lowest Observable Adverse Effect Concentration | SDS | Safety Data Sheet |
| µg/m³ | microgram per cubic meter of air | STEL | Short-term Exposure Limit |
| mg/m³ | milligram per cubic meter of air | TLV | Threshold Limit Value |
| mppcf | million particles per cubic foot | TWA | Time-weighted Average |
| MSHA | Mine Safety and Health Administration | UEL | Upper Explosive Limit |
| NFPA | National Fire Protection Association | | |

Disclaimer: This information is taken from sources or based upon data believed to be reliable. However, Universal Stainless & Alloy Products, Inc. makes no warranty as to the absolute correctness or sufficiency of any of the foregoing or that additional or other measures may not be required under particular conditions.

This SDS covers the following grades of Specialty Steel:

| Grade Group | Grades |
|-------------------------|--|
| Austenitic | 302, 303, 303SE, 304/304L, 309/309S, 310/310S, 316/316L, 317L, 321, 347, 2205, F11, F51, F9, F91, 2304 |
| Ferrite & Martensitic | 403Cb, 403/410, 410CB, 405, 416, 418 (Greek Ascoloy), 420, 420F, 422, 430, 430F, 431, 440A, 440C, 440FSE, 446, H46, FV535, Jethete, 13-5-2 |
| Precipitation Hardening | 15-5, 16-5, 16-6, 17-4, 17-7, 450 |
| High Temp | 330, 330Cb, A-286, 2550, NCAS4 |
| CrNiMn | N32 (XM-28), N33 (XM-29), N40 (21-6-9), N50 (XM-19), N60 (UNS 21800) |
| Low Alloy (VAR) | 300M, 4330, 4340, 4620, 52-100, 6150, 9310, HP9430, D6AC, Nitriding 135, Nitriding N, HyTuf, 300M, 9315 |
| Premium VIM Melt | 13-8, 316/316L, 4340, 4343, 625, 718, 925, 9310, A286, X53, Alloy 100, Alloy 455, Maraging 250, Maraging 300, M50, M50NiL, CRV, 263, CMV |
| Tool Steel | A2, A6, A9, Chipper, D2, H11, H13, L6, M2, M50, O1, O6, S5, S7, D2WT |